

Produkt Name		Product Name	HF2518-12M
Brennweite [mm] (Designwert)	Focal length [mm] (design value)		25 (25.07)
Blende (F-Nummer)	Iris range (Fnumber)		F1.8-F22
Bildwinkel	Angle of view		20.0° × 15.1°(2/3")
Arbeitsabstand (von der Vorderseite des Objektivtubus) [mm]	Working distance (from front of lens barrel) [mm]		∞ - 100
Fokuseinstellung	Operation of focus		Manual
Blendensteuerung	Operation of iris		Manual
Filtergewinde [mm]	Filter thread [mm]		M30.5 x 0.5
Anschluss	Mount		C-mount
Gewicht (ca.) [g]	Weight (approx.) [g]		85
Sensorgröße (maximal)	Sensor size (max.)		1/1.2"
Hintere Brennweite (in Luft) [mm]	Back focal length (in air) [mm]		16.359
Auflagemaß [mm]	Flange back [mm]		17.526
Austrittspupillenposition (vom Bildsensor) [mm]	Exit pupil position (from image plane) [mm]		-78.309
Vordere Hauptpunktposition (vom Anschluss) [mm]	Front principal point (from Mount) [mm]		-2.54
Hintere Hauptpunktposition (vom Anschluss) [mm]	Rear principal point (from Mount) [mm]		-7.42
Abstand zwischen den Hauptpunkten [mm]	Distance between the principal points [mm]		-4.88
TV-Verzerrung [%]	TV distortion [%]		0.0
Abmessungen [mm]	Dimension [mm]		φ33 × 53.1
Relative Beleuchtung [%] (Blende: bei voller Öffnung, Bildhöhe: diagonal)	Relative illumination [%] (Aperture: at full open, Image height: at diagonal)		51.25
Betriebstemperaturbereich	Operation Temperature Range		-10°C ~ +50°C

* Diese Produktspezifikationen und das äußere Erscheinungsbild entsprechen dem Stand zum Zeitpunkt dieser Pressemitteilung (15. März 2016) und können ohne vorherige Ankündigung geändert werden.

01. April 2017

GK VISION GmbH - VISIONTECHNIK
Eggerstedter Weg 18
25421 Pinneberg

Tel.: +49 (0) 4101 805 0028
E-Mail: info@visiontechnik.de
Website: www.visiontechnik.de

型番	Product Name	HF2518-12M
焦点距離 [mm]	Focal length [mm] (design value)	25 (25.07)
絞り (F値)	Iris range (Fnumber)	F1.8-F22
画角 (H × V)	Angle of view	20.0° × 15.1°(2/3")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance (from front of lens barrel) [mm]	∞ - 100
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of iris	Manual
フィルタ径 [mm]	Filter thread [mm]	M30.5 x 0.5
マウント	Mount	C-mount
質量 (約) [g]	Weight (approx.) [g]	85
適合センサーサイズ (最大)	Sensor size (max.)	1/1.2"
バックフォーカス (空気換算長) [mm]	Back focal length (in air) [mm]	16.359
フランジバック [mm]	Flange back [mm]	17.526
射出瞳位置 (結像面より) [mm]	Exit pupil position (from image plane) [mm]	-78.309
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]	-2.54
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	-7.42
主点間隔 [mm]	Distance between the principal points [mm]	-4.88
TVディストーション [%]	TV distortion [%]	0.0
外形寸法 [mm]	Dimension [mm]	φ33 × 53.1
周辺光量比 (開放・対角端) [%]	Relative illumination [%] (Aperture: at full open, Image height: at diagonal)	51.25
使用温度範囲	Operation Temperature Range	-10°C ~ +50°C

* These product specifications and external appearances are as of the time of this press release (March 15, 2016) and subject to change without prior notice.

01. April 2017

GK VISION GmbH - VISIONTECHNIK
Eggerstedter Weg 18
25421 Pinneberg

Tel.: +49 (0) 4101 805 0028
E-Mail: info@visiontechnik.de
Website: www.visiontechnik.de