

Produkt Name		Product Name	HF35XA-5M
Brennweite [mm] (Designwert)	Focal length [mm] (design value)		35 (35.16)
Blende (F-Nummer)	Iris range (Fnumber)		F1.9-F16
Bildwinkel	Angle of view		14.2° × 10.7° (2/3")
Arbeitsabstand (von der Vorderseite des Objektivtubus) [mm]	Working distance (from front of lens barrel) [mm]		∞ - 200
Fokuseinstellung	Operation of focus		Manual
Blendensteuerung	Operation of iris		Manual
Filtergewinde [mm]	Filter thread [mm]		M25.5 x 0.5
Anschluss	Mount		C-mount
Gewicht (ca.) [g]	Weight (approx.) [g]		60
Sensorgroße (standard)	Sensor size (std.)		2/3" (3.45µm)
Sensorgroße (maximal)	Sensor size (max.)		1/1.2" (4.5µm)
Hintere Brennweite (in Luft) [mm]	Back focal length (in air) [mm]		18.50
Auflagemaß [mm]	Flange back [mm]		17.526
Eintrittspupillenposition (vom Anschluss) [mm]	Entrance pupil position (from Mount) [mm]		-7.78
Austrittspupillenposition (vom Bildsensor) [mm]	Exit pupil position (from image plane) [mm]		-37.19
Vordere Hauptpunktposition (vom Anschluss) [mm]	Front principal point (from Mount) [mm]		-6.30
Hintere Hauptpunktposition (vom Anschluss) [mm]	Rear principal point (from Mount) [mm]		-17.63
Abstand zwischen den Hauptpunkten [mm]	Distance between the principal points [mm]		-11.33
TV-Verzerrung [%]	TV distortion [%]		0.10
Abmessungen [mm]	Dimension [mm]		φ29.5 × 41.5
Hauptstrahlwinkel [°]	Chief Ray Angle [°]		8.33
Relative Beleuchtung [%] (Blende: F4.0, Bildhöhe: diagonal)	Relative illumination [%] (Aperture: F4.0, Image height: at diagonal)		96
Relative Beleuchtung [%] (Blende: bei voller Öffnung, Bildhöhe: diagonal)	Relative illumination [%] (Aperture: at full open, Image height: at diagonal)		50
Betriebstemperaturbereich	Operation Temperature Range		-10°C ~ +50°C

*Diese Spezifikationen können ohne vorherige Ankündigung geändert werden.

10. May 2019

GK VISION GmbH - VISIONTECHNIK
Eggerstedter Weg 18
25421 Pinneberg

Tel.: +49 (0) 4101 805 0028
E-Mail: info@visiontechnik.de
Website: www.visiontechnik.de

型番	Product Name	HF35XA-5M
焦点距離 [mm]	Focal length [mm] (design value)	35 (35.16)
絞り (F値)	Iris range (Fnumber)	F1.9-F16
画角 (H × V)	Angle of view	14.2° × 10.7° (2/3")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance (from front of lens barrel) [mm]	∞ - 200
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of iris	Manual
フィルタ径 [mm]	Filter thread [mm]	M25.5 x 0.5
マウント	Mount	C-mount
質量 (約) [g]	Weight (approx.) [g]	60
適合センサーサイズ (標準)	Sensor size (std.)	2/3" (3.45μm)
適合センサーサイズ (最大)	Sensor size (max.)	1/1.2" (4.5μm)
バックフォーカス (空気換算長) [mm]	Back focal length (in air) [mm]	18.50
フランジバック [mm]	Flange back [mm]	17.526
入射瞳位置 (マウント面から) [mm]	Entrance pupil position (from Mount) [mm]	-7.78
射出瞳位置 (結像面より) [mm]	Exit pupil position (from image plane) [mm]	-37.19
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]	-6.30
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	-17.63
主点間隔 [mm]	Distance between the principal points [mm]	-11.33
TVディストーション [%]	TV distortion [%]	0.10
外形寸法 [mm]	Dimension [mm]	φ29.5 × 41.5
主光線入射角度 [°]	Chief Ray Angle [°]	8.33
周辺光量比 (F4.0・対角端) [%]	Relative illumination [%] (Aperture: F4.0, Image height: at diagonal)	96
周辺光量比 (開放・対角端) [%]	Relative illumination [%] (Aperture: at full open, Image height: at diagonal)	50
使用温度範囲	Operation Temperature Range	-10°C ~ +50°C

*These specifications are subject to change without notice.

10. May 2019

GK VISION GmbH - VISIONTECHNIK
Eggerstedter Weg 18
25421 Pinneberg

Tel.: +49 (0) 4101 805 0028
E-Mail: info@visiontechnik.de
Website: www.visiontechnik.de