



OPT CH1 Series Area Scan Cameras

OPT-CH1-M050-XGG3-02


- Optical fiber transmission with a bandwidth of 10 Gbps, the transmission distance up to 300m.
- Support ISP functions including Gamma, LUT, Black level, Brightness and Contrast etc.
- Support Hardware Trigger, Software Trigger, Free Run Mode.
- Built-in large-capacity frame cache, used for data transmission or image retransmission in burst mode.
- Low power consumption and fanless design, no vibration, no dust accumulation.
- Compatible with GigE Vision V2.0 Protocol and GenICam Standard, convenient for third-party connection.

Specification


Model	Sensor model	Sensor type	Shutter type	Resolution	Frame rate	Pixel size	Sensor size	Mono/Color
OPT-CH1-M050-XGG3-02	GMAX3405	CMOS	Global	2448 × 2048	164 fps	3.4 μm×3.4 μm	2/3"	Mono

Name	5 MP Mono 10GigE (SFP+) Area Scan Camera
Pixel format	Mono 8/10/10Packed/12/12Packed
Max Frame rate	164 fps@2448 × 2048 Mono 8
Dynamic range	68.9 dB
SNR	39.2 dB
Gain	1 dB ~ 16 dB
Exposure time	6 μs ~ 4 s
Trigger mode	Software Trigger/Hardware Trigger/Free Run Mode
Reverse image	Horizontal Reverse, Vertical Reverse
Binning	No Support
Data interface	10GigE (SFP+)
I/O interface	12-pin Hirose interface power supply: 2 × Opto-isolated input, 2 × Opto-isolated output
Power supply	Voltage range DC: 12 VDC to 24 VDC
Power consumption	7.0 W@24 VDC
Lens mount	C-Mount
Dimension	76 mm×76 mm×62.7 mm (not including lens mount and rear case connector)
Weight	≈ 470 g
Temperature	Working temperature: 0 °C to 50 °C, Storage temperature: 0 °C to 80 °C
Operating system	Windows 7/10/11 32/64bits, Linux 64bits, MacOS 64bits
Compatibility	GigE Vision V2.0, GenICam
Certification	/


Spectral Response



Dimension (mm)



I/O Interface Description



PIN	Signal	Description
1	GND	Power ground
2	POWER	DC 24V Camera power supply
3	NC	reserved
4	NC	reserved
5	NC	reserved
6	NC	reserved
7	OUT_GND	Opto-isolated output ground
8	Lineout1	Opto-isolated output 1
9	Lineout2	Opto-isolated output 2
10	IN_GND	Opto-isolated input ground
11	Line2	Opto-isolated input 2
12	Line1	Opto-isolated input 1



OPT MACHINE VISION TECH CO.,LTD.

No. 66 Xingfa South Road, Chang'an Town, Dongguan City, Guangdong Province, China

Tel: +86-769-82716188

Fax: +86-769-81606698

Email: optmv@optmv.com

Web: www.optmv.net



Web



LinkedIn