

Optical Specification	
Model	OPT-CH10-110FC-F8
Optical Configuration	Telecentric
Working Distance (mm)	110±2
Magnification	1.0X
Sensor Ø (mm)	11.0(2/3")
Aperture	F8
Telecentricity	0.10°
NA	0.06217
Distortion	<0.1%
Depth of Field (mm)	0.66
Resolution (µm)	4.2
Image MTF30 (lp/mm)	120
Field of View Ø (mm)	11.00
O/I Distance (mm)	237.4
Mount	C-Mount
Weight (kg)	0.25
Size (mm)	Ø 36×109.9
Filter Thread (mm)	M34×0.5-6H
Working Temperature	0°C~+40°C


[1]Resolution:The resolution is the image resolution.
[2]DOF evaluation formula for telecentric lenses:

DOF(mm)= $\frac{F\# \times P \times k}{\beta \times \beta}$

F#:The real F-number of a lens when used
P:Sensor pixel size (5.5 µm used here)
β:Lens magnification
k:The parameter based on application (measurement,
k=0.015; defect detection, k=0.008; 0.015 used here)

At the borders of DOF,the image can still be used for measurement.But only half of the nominal DOF should be used to get a sharp image.


[3]The lens supports dedicated surface illumination. For objects with low reflectivity, a dedicated surface light source is recommended for better illumination. OPT-FL3118-CH-X is available as an option.



View Angle		Item	Signature	Date	OPT Machine Vision Tech Co., Ltd.			
		Drawing						
Standard Difference	IT14	Design			All Rights Reserved			
		Check						
Drawing Code		Scale	1:1		Name	OPT-CH10-110FC-F8		
		Paper Size	A4		Unit	mm	Page 1 / 2	Version V1.0

A				B	C	D			
Model	Color	Voltage	Power			JST SMR-02V-B, 2 Pin or Compactible Connector 	Pin	Polarity	Wire Color
OPT-FL3118-CH-R	Red	24V	2.88W				1	+	/
OPT-FL3118-CH-G	Green	24V	2.88W				2	-	/
OPT-FL3118-CH-B	Blue	24V	2.88W						
OPT-FL3118-CH-W	White	24V	2.88W						

JST SMR-02V-B, 2 Pin
or Compactible Connector



View Angle	 	Item	Signature	Date	 OPT Machine Vision Tech Co., Ltd. Machine Vision				
		Drawing							
Standard Difference	IT14	Design			All Rights Reserved				
		Check							
Drawing Code		Scale			Name	OPT-FL3118-CH-X			
		Paper Size	A4		Unit	mm	Page 2 / 2	Version	V1.0.1