



OPT CL1 Series Line Scan Cameras



OPT-CL1-M16-L3-02


- Camera Link interface, Support Base, Medium, Full and 80-bit Four configuration modes.
- Support ISP functions including FFC, Black level, LUT, Gamma etc.
- Support Internal Trigger and External Trigger.
- Support multiple image data formats output, ROI, Reverse, etc.
- Support DC12~24V wide-voltage power supply.
- Compatible with Camera Link Protocol and GenICam Standard.

Specification


Model	Sensor type	Resolution	Line rate	Pixel size	Lens mount	Mono/Color
OPT-CL1-M16-L3-02	CMOS	16384 × 1	50 kHz	3.5 μm×3.5 μm	M72*0.75	Mono

Name	16K Mono Camera Link Line Scan Camera
Pixel format	Mono 8/10@2/4/8Tap, Mono 8@10Tap
Max. line rate	Mono 8: 10 kHz@2Tap, 20 kHz@4Tap, 40 kHz@8Tap, 50 kHz@10Tap
Dynamic range	56.6 dB
SNR	37 dB
Gain	1 dB ~ 15.5 dB
Exposure time	5 μs ~ 50 ms
Trigger mode	Internal Trigger, External Triggerr
Binning	No Supports
Data interface	Camera Link SDR
Power supply	6-pin Hirose interface power supply, 12 VDC to 24 VDC
Power consumption	4.44 W@24 VDC
Dimension	76 mm(W) × 76 mm(H) × 37.8 mm(D)
Weight	≈ 360 g
Temperature	Working temperature:0 ~ 50℃, Storage temperature:0 ~ 80℃
Operating system	Windows 7/10/11 32/64bits
Compatibility	Camera Link, GenICam
Certification	CE, RoHS, FCC


Spectral Response



Dimension (mm)



I/O Interface Description



PIN	Signal	Description
1	Power	DC 12V~24V Camera power
2	Power	DC 12V~24V Camera power
3	Power	DC 12V~24V Camera power
4	GND	Power ground
5	GND	Power ground
6	GND	Power ground



OPT MACHINE VISION TECH CO.,LTD.

No. 66 Xingfa South Road, Chang'an Town, Dongguan City, Guangdong Province, China

Tel: +86-769-82716188

Fax: +86-769-81606698

Email: optmv@optmv.com

Web: www.optmv.net



Web



LinkedIn