



OPT CL1 Series Line Scan Cameras

OPT-CL1-M2-G3-01

- Gigabit Ethernet interface, transmission distance of 100m without relay.
- Support ISP functions including FFC, Black level, LUT, Gamma etc.
- Support Software Trigger, Hardware Trigger, Free Run Mode.
- Built-in large cache for data transfer or image retransmission in burst mode.
- Support multiple image data formats output, ROI, Reverse, etc.
- Compatible with GigE Vision V2.0 Protocol, GenICam Standard, and third-party software based on these protocol and standard.




Specification


Model	Sensor type	Resolution	Line rate	Pixel size	Lens mount	Mono/Color
OPT-CL1-M2-G3-01	CMOS	2048 × 1	57 kHz	14 μm×14 μm	M42*1.0	Mono

Name	2K Mono GigE Line Scan Camera
Pixel format	Mono 8/10/10Packed/12/12Packed
Max. line rate	57 kHz@Mono 8
Dynamic range	69.9 dB
SNR	44.5 dB
Gain	1 dB ~ 16 dB
Exposure time	10 μs ~ 50 ms
Trigger mode	Internal Trigger, External Trigger
Binning	No Supports
Data interface	GigE PoE
Power supply	12-pin Hirose interface power supply, Voltage range:12 ~ 24VDC
Power consumption	2.5 W@24 VDC
Dimension	62 mm(W) × 62 mm(H) × 38.6 mm(D)
Weight	≈ 220 g
Temperature	Working temperature:0 ~ 50°C, Storage temperature:0 ~ 80°C
Operating system	Windows 7/10/11 32/64bits, Linux 64bits, MacOS 64bits
Compatibility	GigE Vision V2.0, GenICam
Certification	CE, RoHS, FCC


Spectral Response



Dimension (mm)



I/O Interface Description



PIN	Signal	Description
1	GND	Power Ground
2	Power	DC 24V Camera Power Supply
3	EncoderA+	Encoder Differential signal Input A+
4	EncoderA-	Encoder Differential signal Input A-
5	EncoderB-	Encoder Differential signal Input B-
6	EncoderB+	Encoder Differential signal Input B+
7	OUT_GND	Opto-isolated Output ground
8	Lineout1	Opto-isolated Output 1
9	Lineout2	Opto-isolated Output 2
10	IN_GND	Opto-isolated Input ground
11	Line2	Opto-isolated Input 2
12	Line1	Opto-isolated Input 1



OPT MACHINE VISION TECH CO.,LTD.

No. 66 Xingfa South Road, Chang'an Town, Dongguan City, Guangdong Province, China

Tel: +86-769-82716188

Fax: +86-769-81606698

Email: optmv@optmv.com

Web: www.optmv.net



Web



LinkedIn