



OPT CL1 Series Line Scan Cameras



OPT-CL1-M8-XG3-02


- Optical fiber transmission with a bandwidth of 10 Gbps, the transmission distance up to 300 meters.
- Support ISP functions including FFC, Black level, LUT, Gamma etc.
- Support Software Trigger, Hardware Trigger, Free Run Mode.
- Low power consumption and fanless design, no vibration, no dust accumulation.
- Support multiple image data formats output, ROI, Reverse, etc.
- Compatible with GigE Vision V2.0 Protocol, GenICam Standard, and third-party software based on these protocol and standard.

Specification


Model	Sensor type	Resolution	Line rate	Pixel size	Lens mount	Mono/Color
OPT-CL1-M8-XG3-02	CMOS	8192 × 1	125 kHz	7 μm × 7 μm	M72*0.75	Mono

Name	8K Mono 10GigE (SFP+) Line Scan Camera
Pixel format	Mono 8/10/10Packed/12/12Packed
line rate	125 kHz@Mono 8
Dynamic range	63.3 dB
SNR	40 dB
Gain	1 dB ~ 15.5 dB
Exposure time	5 μs ~ 50 ms
Trigger mode	Internal Trigger, External Trigger
Binning	No Supports
Data interface	10 GigE (SFP+)
Power supply	12-pin Hirose interface power supply, Voltage range: 12 ~ 24 VDC
Power consumption	5.44 W@24 VDC
Dimension	76 mm(W) × 76 mm(H) × 69.8 mm(D)
Weight	≈ 535 g
Temperature	Working temperature: 0 ~ 50°C, Storage temperature: 0 ~ 80°C
Operating system	Windows 7/10/11 32/64bits, Linux 64bits, MacOS 64bits
Compatibility	GigE Vision V2.0, GenICam
Certification	CE, RoHS, FCC


Spectral Response



Dimension (mm)



I/O Interface Description



PIN	Signal	Description
1	GND	Power ground
2	Power	DC 24V Camera Power Supply
3	EncoderA+	Encoder Differential signal Input A+
4	EncoderA-	Encoder Differential signal Input A-
5	EncoderB-	Encoder Differential signal Input B-
6	EncoderB+	Encoder Differential signal Input B+
7	OUT_GND	Opto-isolated Output ground
8	Lineout1	Opto-isolated Output 1
9	Lineout2	Opto-isolated Output 2
10	IN_GND	Opto-isolated Input ground
11	Line2	Opto-isolated Input 2
12	Line1	Opto-isolated Input 1



OPT MACHINE VISION TECH CO.,LTD.

No. 66 Xingfa South Road, Chang'an Town, Dongguan City, Guangdong Province, China
Tel: +86-769-82716188 Fax: +86-769-81606698
Email: optmv@optmv.com Web: www.optmv.net



Web



LinkedIn