


Optical Specification		
Model		OPT-F2528-29M
Focal Length (mm)		25
Adjuston Type		Manual
Aperture		F2.8-F32
Sensor $\varnothing$ (mm)		44
Working Distance (mm)		140~ ∞
Mag. at MOD		0.1522X at WD140
Resolution (μ m)		5
Distortion		<0.9%
Back Focal Length (mm)		26.4
Effective Diameter	Front $\varnothing$ (mm)	53.0
	Back $\varnothing$ (mm)	26.0
Field Angle	1" (12.8 $\times$ 9.6 $\times$ 16)	28.7 $^{\circ}$ $\times$ 21.7 $^{\circ}$ $\times$ 35.5 $^{\circ}$
	4/3" (18.88 $\times$ 10.6 $\times$ 21.6)	39.6 $^{\circ}$ $\times$ 30.2 $^{\circ}$ $\times$ 48.5 $^{\circ}$
	44mm(36 $\times$ 24 $\times$ 43.3)	70.3 $^{\circ}$ $\times$ 55.7 $^{\circ}$ $\times$ 82.7 $^{\circ}$
Mount		F-Mount
Weight (kg)		0.71
Size (mm)		$\varnothing$ 80 $\times$ 95.75
Filter Thread (mm)		M77 $\times$ 0.75-6H
Working Temperature		-20 $^{\circ}$ C $\sim$ +60 $^{\circ}$ C



View Angle		Item	Signature	Date	 OPT Machine Vision Tech Co., Ltd.			
		Drawing						
Standard Difference	IT14	Design			All Rights Reserved			
		Check						
Drawing Code		Scale	1:1		Name	OPT-F2528-29M		
		Paper Size	A4		Unit	mm	Page 1 / 1	Version V3.0