


Optical Specification	
Model	OPT-HP10-110C-F11
Optical Configuration	Telecentric
Working Distance (mm)	110±2
Magnification	1.0X
Sensor Ø (mm)	18.4(1.1")
Aperture	F11
Telecentricity	0.10°
NA	0.0454
Distortion	<0.1%
Depth of Field(mm)	0.91
Resolution (μm)	5.5
Image MTF30(LP/mm)	90
Field of View Ø (mm)	18.40
O/I Distance(mm)	273.6
Mount	C-Mount
Weight (kg)	0.41
Size (mm)	Ø 45.0×146.1
Filter Thread (mm)	M42×0.5-6H
Working Temperature	-20℃~+60℃



[1]Resolution:The resolution is the image resolution.
[2]DOF evaluation formula for telecentric lenses:

DOF(mm)= $\frac{F\# \times P \times k}{\beta \times \beta}$

F#:The real F-number of a lens when used
P:Sensor pixel size (5.5 μm used here)
β:Lens magnification
k:The parameter based on application (measurement, k=0.015; defect detection, k=0.008; 0.015 used here)

At the borders of DOF,the image can still be used for measurement. But only half of the nominal DOF should be used to get a sharp image.

View Angle		Item	Signature	Date	 OPT Machine Vision Tech Co., Ltd.			
		Drawing						
Standard Difference	IT14	Design			All Rights Reserved			
		Check						
Drawing Code		Scale	9:10		Name	OPT-HP10-110C-F11		
		Paper Size	A4		Unit	mm	Page 1 / 1	Version V1.0